


Mitsubishi Electric introduces the R32 MSZ-EF Series, expanding our line-up in the low Global Warming Potential (GWP) refrigerant. With just one third of the GWP of the R410A we aim to help reduce the household carbon footprint. The streamlined wall mounted indoor units have contemporary clean lines, expressing sophistication and quality, and is available in 3 stylish colours.



## **Quiet Operation**

The "Quiet" fan speed setting ensures super quiet operation below 21dB\*. Perfect for the bedroom; it's so quiet you'll check to see if it's on.
\*Model 25/35 only.



### Nano Platinum Filter

The Nano Platinum Deodorising Filter reduces airborne bacteria while improving air quality. The optional Electro Static Anti-Allergy Enzyme Filter assists in the reduction of common allergens.



#### **NEW** Backlit Controller

With an easy to read backlit display and a variety of operating modes at the touch of a button. This controller features a weekly and 24 hour timer, On/Off timer to set operating times on a daily basis. The 'i-Save' mode recalls the preset temperature.

# **Features**

- Capacity Range: 2.5/3.5/4.2/5.0kW
- Unit Dimensions:895 (w) x 195 (d) x 299mm (h)
- Built-In Weekly Timer
- Quiet 21dB Noise Level in 'Quiet Mode' (EF25/35)
- Nano Platinum Filter
- Appealing design matches any room décor
- Colour: Classic White, Matte Silver and Glossy Black

# **Product Specifications**

Indoor Unit				MSZ-EF25VG (W/B/S) -A1	MSZ-EF35VG (W/B/S) -A1	MSZ-EF42VG (W/B/S) -A1	MSZ-EF50VG (W/B/S) -A
Outdoor Unit				MUZ-EF25VG-A1	MUZ-EF35VG-A1	MUZ-EF42VG-A1	MUZ-EF50VG-A1
Refrigerant					R	32	I
	Capacity [Rated]		kW	2.5	3.5	4.2	5.0
	Capacity [Min-Max]		kW	0.9 - 3.4	1.1 - 4.0	0.9 - 4.6	1.4 - 5.4
	Total Input [Rated]		kW	0.54	0.91	1.20	1.55
Cooling	Total Input [Min-Max]		kW	0.23 - 1.15	0.21 - 1.50	0.15 - 1.93	0.30 - 1.98
	EER			4.63	3.85	3.50	3.23
	AEER			4.60	3.83	3.49	3.22
	Star Rating			4.5	3.0	2.0	1.5
	New Star Rating Hot & Humid Mixed Cold		Hot & Humid	4.5	3.5	3	.0
			Mixed	4.0	3.5	3.0	
			Cold	4.0	3.5	3.0	
	Running [Rated]	Current	A	3.0	4.2	5.4	6.9
		In [Quiet-Lo- Mid-Hi-SHi]	dB(A)	19 - 42	21 - 42	28 - 43	30 - 43
	SFL	Out [PWL]	dB(A)	47 (58)	49 (62)	50 (62)	52 (65)
	Air Volume (In) [Quiet- SHi]		L/S	67 -	67 - 175 97 - 187 97 - 188		97 - 188
Heating	Capacity [Rated]		kW	3.2	4.0	5.4	5.8
	Capacity [Min-Max]		kW	1.0 - 4.2	1.3 - 5.1	1.3 - 6.3	1.4 - 7.5
			kW	0.70	0.95	1.455	1.56
	Total Input [Min-Max] kV		kW	0.23 - 1.17	0.21-1.33	0.26 -2.05	0.30 - 2.64
	СОР			4.57	4.21	3.71	3.72
	ACOP			4.55	4.20	3.70	3.71
	Star Rating			4.5	4.0	3.0	2.5
	New Star Rating    Hot & Humid		3.0 2.5				
			2.5				
			2.5		2.0		
	Running [Rated]	Current	A	3.5	4.4	6.5	7.1
	SPL	In [Quiet- SHi]	dB(A)	21 - 45	21 - 46	28 - 48	30 - 49
		Out [PWL]	dB(A)	48 (61)	50 (63)	51 (64)	52 (65)
	Air Volur SHi]	ne (In) [Quiet-	L/S	67 - 198	67 - 212	92 - 220	107 - 243
Piping	Diameter [Gas/Liquid]		mm	ø9.52/ø6.35			
	Max. Length/Height		m	20/12 30/15			30/15
Indoor Unit	Input (Cooling/ Heating) [Rated]		w	20/26	20/30	23/33	23/43
			mm	299 × 885 × 195			
	Weight k		kg	11.5			
Outdoor Unit	Dimensions [HxWxD]		mm		550 × 800 × 285		714 × 800 × 285
	Weight		kg	31	34	35	40
	Breaker Size		A	1	0	12	16
Guara <u>nteed</u>	-		Cooling °C	-10 ~ 46			
Outdoor]			Heating °C	-15 ~ 24			
Refrigerant .	Amount [	Pre-Charge]	kg	0.62		0.74	









MitsubishiElectric.com.au

<sup>\*</sup>Optional upgrade adapter required per unit. Requires an Internet connection and the App downloaded from the App Store or Google Play Store on your smartphone or tablet with the latest Operating System available. \*To use Amazon Alexa to control your air conditioner, you will need an Amazon Alexa Echo device. \*To use Google Assistant to control your air conditioner, you will need a Google Home smart speaker.